

# DATACARD® CD800™ ENTERPRISE-CLASS CARD PRINTER SPECIFICATIONS



## CD800™ Printer Standard Features

**Print technology**  
Direct-to-card dye-sublimation/resin thermal transfer

**Print capabilities**  
One-sided (simplex) or optional two-sided (duplex), edge-to-edge printing  
Full-color and monochrome printing capability  
Alphanumeric text, logos and digitized signatures  
1D/2D bar code images  
Printer pooling/sharing

**Print resolution**  
Standard mode:  
300 x 300 dots per inch; standard text, bar code and graphics printing  
High Quality (HQ\*) mode:  
300 x 600 dots per inch; enhanced text, bar code and graphics printing  
300 x 1200 dots per inch; enhanced text and bar code printing  
256 shades per color panel

**Print quality**  
Datacard® TrueMatch™ printing technology  
Ability to conform to sRGB standard  
Flexible color management options

**Print speed**  
Full-color printing: up to 220 cards per hour, one-sided (YMCKT\*), up to 165 cards per hour, two-sided (YMCKT-K\*)  
Monochrome printing: up to 1,000 cards per hour, one-sided (black HQ\*)

**Printer memory**  
128 MB standard

**Encoding**  
Magnetic stripe encoding  
ISO 7811, three track high- and low-coercivity  
JIS Type II single-track option

**Card capacity**  
Automatic feed: 100-card input for 0.030 in. (0.76 mm) cards; 25-card output standard  
Front exception card slot  
Separate reject location and holding tray; 10-card capacity  
Input hopper empty detection

**Printer display**  
Printer status messages  
Multiple backlight settings  
International languages available: English, Spanish, German, Italian, Japanese

**Printer driver**  
Split-panel YMCKT feature for dual-sided printing  
Adjustable color controls with image preview  
Pre-set area to block printing on magnetic stripe, with escapes for custom areas  
Utilizes Windows® XPS-based technology for high-fidelity printing  
Secure disabling of card remake  
Software Development Kit (SDK) for Windows operating system driver  
User interface languages available: English, French, German, Italian, Japanese, Simplified Chinese, Traditional Chinese, Korean, Portuguese (Brazil), Russian, Spanish, Romanian and Polish

**User-friendly operation**  
Printer messages display on LCD panel  
Graphical display on Windows 7 operating system  
Easy, fast installation

Card remake standard with cancel option  
Operator-replaceable printhead  
Front panel soft power button  
Datacard® Certified Supplies featuring Intelligent Supplies Technology™  
Automatic identification and validation for ribbons  
Adjustable low ribbon and cleaning cycle alerts  
Ribbon saver  
Warranties  
30-month standard depot warranty  
30-month printhead warranty (no pass restrictions)

## CD800 Printer Options

**Multi-Hopper**  
Six-compartment multi-hopper  
Six 100-card hoppers, 600-card total capacity  
Two-sided (duplex) printing (field-upgradeable)  
Smart card personalization  
Factory options:  
Single-wire contact/contactless all-in-one encoder (read/write) for MIFARE, ISO7816, ISO14443 A/B, ISO15693, ISO FeliCa. DESFire available by Dec. 2012.  
Two-wire contact/contactless all-in-one encoder (read/write) for MIFARE/DESFire, ISO7816, ISO14443, A/B  
Field upgradeable options:  
Single-wire contact/contactless all-in-one encoder (read/write) for MIFARE, ISO7816, ISO14443 A/B, ISO15693, ISO FeliCa. DESFire available by Dec. 2012.  
Two-wire contact/contactless all-in-one encoder (read/write) for MIFARE/DESFire, ISO7816, ISO14443, A/B  
iCLASS® by HID, read/write encoder or read-only PC Prox by HID, read-only  
Third-party OEM smart card option-ready (for contactless readers only – encoder not included)

**OpenCard**  
Factory option only; single- or dual-sided printing; full-color and/or monochrome printing; ethernet or USB

**End-user upgradeable options**  
Extended 100-card output hopper (available for single-hopper)  
Extended 200-card input hopper (available for single-hopper)  
Kensington® security lock for printer

## CD800 Printer Supplies

**Print ribbon kits - color**  
Full-color with resin black and topcoat panel, YMCKT\*, 250 images  
Full-color with resin black and topcoat panel, YMCKT\*, 500 images  
Full-color short panel with resin black and topcoat panel, ymckT\*, 650 images  
Resin black and topcoat panel, KT\*, 1000 images  
Full-color with resin black and topcoat panel on front, resin black on back, YMCKT-K\*, 375 images (duplex)  
Full-color with resin black and topcoat panel on front, resin black and topcoat panel on back, YMCKT-KT\*, 300 images (duplex)  
Resin black with inline double topcoat panel on front, topcoat panel on back, KTT\*, 750 images (duplex)

**Print ribbon kits - monochrome**  
Resin black HQ\*, 500 images

Resin black HQ\*, dark blue, white, red, green, silver, gold, metallic silver, metallic gold, 1500 images  
New, improved scratch-off, 1500 images

## CD800 Printer Specifications

**Physical dimensions**  
One-sided printing: L 17.4 in. x W 8.8 in. x H 8.8 in. (44.2 cm x 22.4 cm x 22.4 cm)  
Two-sided printing: L 21.2 in. x W 8.8 in. x H 8.8 in. (53.8 cm x 22.4 cm x 22.4 cm)  
Six-compartment multi-hopper: L 27.5 in. x W 16.5 in. x H 14.5 in. (69.9 cm x 41.9 cm x 36.8 cm)

**Weight**  
One-sided printing: 9.0 lbs (4.1 kg) (depending on options)  
Two-sided printing: 12.0 lbs (5.4 kg) (depending on options)  
Six-compartment multi-hopper: 33 lbs (15 kg)

**Electronic requirements**  
100/120V, 50/60 Hz  
220/240V, 50/60 Hz

**Plastic cards accepted**  
ISO ID-1/CR-80 size cards 3.370 in. x 2.125 in. (85.6 mm x 53.98 mm)  
PCV with glossy laminate surface  
Select key fob cards (ISO ID-1/CR-80 size cards)  
Datacard® StickiCard™ adhesive-backed plastic cards

**Card thickness accepted**  
0.010 in. to 0.037 in. (0.254 mm to 0.939 mm)

**Operating environment**  
60°F to 95°F (15°C to 35°C)  
20% to 80% non-condensing humidity

**Storage environment**  
5°F to 140°F (-15°C to 60°C)  
10% to 90%, non-condensing humidity

**Connectivity**  
Bidirectional USB 2.0 high speed  
Ethernet 10 Base-T/100-Base-TX (with activity light)

**Operating system support for printer driver**  
Windows 8 (32 and 64 bit)  
Windows 7 (32 and 64 bit)  
Windows XP SP3 (32 bit)  
Windows Server 2012 (64 bit)  
Windows Server 2008 R2 (64 bit)  
Windows Server 2003 R2 (32 bit)

**Agency approvals**  
cULus, FCC, I.C., CE, Ctick, VCCI, RoHS, WEEE, CCC, KCC

**Environment/energy-saving features**  
Biodegradable supply cores made with EcoPure® additive  
Recyclable enclosure plastics (marked with recycle symbol per Resin Identification Code)  
Recyclable packaging

**Included with CD800 printer**  
Printer driver CD, Quick Install Guide and warranty  
ID Centre™ Intro identification software  
Cleaning pen  
Cleaning roller spindle  
USB cable  
Power supply  
Power cord (region-specific)

\*Ribbon type and number of panels; Y=Yellow, M=Magenta, C=Cyan, K=Black, T=Inline Topcoat, HQ=High Quality